197Vk2
19" TFT MONITOR

Panel	19'' (48 cm) TFT Active Matrix LCD, Diagonal Hard Coating (3H), Anti-glare Treatment
Design Line	Value
Pixel / Dot Pitch	0.294mm x 0.294mm
Viewable Image Size (Diagonal)	19''
Display Area	376mm x 301mm
Brightness	300 cd/m² (typ)
Contrast Ratio	3000:1 (DCR)
Typ. Response Time (tr+tf)	2 ms
Viewing Angle	CR=10: 160/160 Degrees
Compatibility	VESA, XGA, SVGA, VGA, Mac®Equipped With VGA Port
Scanning Frequency	Horizontal: 30K~83KHz Vertical: 55~75 Hz
Pixel Frequency	135 MHz
Maximum Resolution	1280x1024@75Hz (Analogue) 1280x1024@75Hz (DVI-D)
Recommended Resolution	1280x1024@60Hz
Resolution Supported	640x400@70Hz, 720x400@70Hz, 832x624@75, 640x480@60/67/72/75Hz, 800x600@56/60/72/75Hz, 1024x768@60/70/75Hz, 1280x1024@60/75Hz
Colours	16.7M
Signal Input	Video: 0.7Vp-p, RGB analogue, Separate Sync: TTL Level, H/V Sync: Positive / Negative, Digital Input: DVI-D
Connectors	Analogue RGB Signal: 15-pin D-sub Male, **DVI-D: 24-pin DVI-D,** Power Input: Universal 100~240VAC,
Power Source	Power Input: Universal 100~240VAC, 50/60Hz
Power Consumption	37 Watts (Max)
Plug & Play	DDC1/2B
EPA ENERGY STAR ®	yes
User Control	Auto Adjust, Menu, On/Off, Eco/Left, Right
Function	Brightness, Contrast, Eco Mode,Gamma(1,2,3),DCR,Focus, Clock, H/V Position, Color Temperature, Color Boost,Picture Boost, OSD Setup, Input select, AUTO Config, Reset,Information
OSD Languages	English, Spanish, French, Portoguese, German, Russian, Italian, Chinese
Speaker	NA
Emissions Standard	
Regulation	UL, CSA, FCC, TUV/GS, CE, ISO 13406-2, Pixel Fault Class II, Windows®XP Logo
Other Features	VVESA Wall Mountable*, Kensington Security Slot
Dimensions (WxHxD)	Monitor: 413 x 413 x 216 Carton:
Weight	Net: 4.85kgs Gross: 6.35kgs
Loading Qty w/pallet	
Warranty	
EAN Code	4038986190220

Note: Specifications are subject to change without notice. *Wall mount arm & bracket not included.

SPECIFICATIONS